

	US UNITS	METRIC UNITS
Total Weight	20.0 oz. PLY 13.3 oz. PSY	620 g PLM 451 g PSM
Roll Width	52" – 54"	132 cm - 137 cm
Backing	Woven	
Tensile (Minimum)	50 x 55 lbf	222 x 245 N
Tear (Minimum)	25 x 25 lbf	111 x 111 N
Federal Spec.	CCC-W-408D, Type II	
WA Spec.	WA-101, Type II	
ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M)) Tunnel Test ¹ Class A Rating Flame Spread - 10 Smoke Developed - 5 NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011	
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices	
Repeat	Vertical Horizontal Nominal Pattern Width Match Information	N/A N/A 51" Reverse Hang, Space Stripes
	1 When applied to GRC board with A-848-B adhesive	2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

Available in 11 Colorways

Expression C822-72	Harmony C822-81
Integrity C822-51	Stability C822-25
Confidence C822-92	Compassion C822-40
Commitment C822-90	Intuitive C822-20
Longevity C822-18	Prosperity C822-50
Connection C822-94	