

	US UNITS	METRIC UNITS
Total Weight	20.0 oz. PLY 13.3 oz. PSY	620 g PLM 451 g PSM
Roll Width	52" – 54"	132 cm - 137 cm
Backing	Woven	
Tensile (Minimum)	50 x 55 lbf	222 x 245 N
Tear (Minimum)	25 x 25 lbf	111 x 111 N
Federal Spec.	CCC-W-408D, Type II	
WA Spec.	WA-101, Type II	
ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M)) Tunnel Test ¹ Class A Rating Flame Spread - 10 Smoke Developed - 5 NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011	
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices	
Repeat	Vertical N/A Horizontal N/A Nominal Pattern Width 51" Match Information Reverse Hang, Random Match	
1	When applied to GRC board with A-848-B adhesive	2
		When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

Available in 12 Colorways

S322-10 Fountain	S322-57 Terrace
S322-12 Portico	S322-60 Citadel
*S322-42 Chamber	S322-65 Acid Stained
S322-48 Monument	S322-80 Plinth
S322-50 Raw	S322-90 Underpass
S322-55 Brutalist	S322-92 Bunker

* These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.